

The listing of pending claims is reproduced below as a convenience to the Examiner:

**Listing of Pending Claims:**

1-3. (Cancelled)

4. (Previously Presented) A driving assembly of an AV system for a vehicle having a tiltable monitor disposed at a front surface of a main body of the AV system, the driving assembly comprising:

a main printed circuit board attached to the main body;

a low-surface chassis disposed at a lower end of the main body;

a slide chassis mounted on the low-surface chassis, said slide chassis moves a lower side of the monitor back and forth and includes a plurality of reinforcement brackets;

a secondary printed circuit board disposed on the low-surface chassis

a motor part mounted to the secondary printed circuit board disposed on the low-surface chassis;

a motor part mounted to the secondary printed circuit board and the low-surface chassis;

a back-and-forth motion member that moves the slide chassis back and forth in response to a rotational force of the motor part; and

a connector which is mounted on the secondary printed circuit board, the connector connects the secondary printed circuit board to the main printed circuit board by a cable for controlling a motor of the motor part, wherein the motor part comprises:

the motor;

the secondary printed circuit board mounted with the connector that is attached to one end of the motor; and

a worm attached to the other hand of the motor, for transferring power from the motor to the back-and-forth motion member.

5-6. (Cancelled)

Attorney Docket: HATO.2110.0002  
Application Serial No. 10/720,350

7. (Previously Presented) The driving assembly of claim 4, wherein the back-and-forth motion member comprises:

a wormwheel engaged with the worm, and

a wheel, one end thereof being engaged with the wormwheel and an other end thereof being engaged with the slide chassis.

8. (Previously Presented) The driving assembly of claim 4, wherein a bracket for supporting the motor part is further mounted on the low-surface chassis.

9. (Previously Presented) The driving assembly of claim 4, wherein at least one reinforcing bracket comprises a c-shape.

10-17. (Cancelled)

18. (Previously Presented) A driving assembly of an AV system that includes a tiltable monitor, the driving assembly comprising:

a low-surface chassis disposed at a lower end of a main body;

a slide chassis mounted on the low-surface chassis, said slide chassis moves a lower side of the tiltable motor back and forth;

a back-and-forth motion member responsive to a motor part mounted on a bracket to the low-surface chassis and which moves the slide chassis back and forth;

a main printed circuit board attached to the main body;

a secondary printed circuit board attached to the motor part;

a connector attached to the secondary printed circuit board;

a cable for connecting the main printed circuit board to the connector on the secondary printed circuit board; and

at least one reinforcing bracket mounted on the slide chassis.

19-24. (Cancelled)

Attorney Docket: HATO.2110.0002  
Application Serial No. 10/720,350

25. (Previously Presented) A driving assembly of an AV system for a vehicle having a tiltable monitor disposed at a front surface of a main body of the AV system, the driving assembly comprising:

- a low-surface chassis disposed at a lower end of the main body;

- a slide chassis mounted on the low-surface chassis, said slide chassis moves a lower side of the monitor back and forth;

- a secondary printed circuit board disposed on the low-surface chassis;

- a motor disposed on the low-surface chassis;

- a connector mounted on the secondary printed circuit board for inputting signals to the motor;

- a back-and-forth motion member that moves the slide chassis back and forth in response to a rotational force of the motor;

- a cable, having a connector attached to a first end, for connecting a first end of the cable to the connector; and

- a main printed circuit board, attached to the main body, and being connected to a second end of the cable;

wherein when the main body is separated from the low-surface chassis, the motor is exposed for visual inspection or replacement, without removing the main printed circuit board from the AV system, and

wherein the driving assembly includes at least a first c-shaped bracket disposed on the slide chassis for reinforcing an elongate hole in the slide chassis.

26. (Previously Presented) The driving assembly of claim 25 wherein the driving assembly includes a second c-shaped bracket disposed on the slide chassis.